

**REMARKS**


The Examiner is advised that the above amendments are being made with respect to the English language translation of the subject application and hence all references are with respect to the certified translation previously filed.

Claims 1-3, 5, 9, and 11 have each been amended to place them in better form for examination and claims 14 through 29 have been added by way of this amendment. Claims 14-29 correspond in modified form to previously cancelled claims 4, 6, 7, 8, 10, 12 and 13.

Favorable consideration and allowance of this application is respectfully requested.

Respectfully submitted,

By:



Richard L. Carlson  
Reg. No. 27,863  
Attorney for Applicant

Harness, Dickey & Pierce, P.L.C.  
P.O. Box 828  
Bloomfield Hills, MI 48303  
(248) 641-1600

January 14, 2002  
RLC/jb

**ATTACHMENT FOR SPECIFICATION AMENDMENTS**

The following is a marked up version of each replacement paragraph and/or section of the specification in which underlines indicates insertions and brackets indicate deletions.

**Page 1, before the first paragraph, please insert the following header:**

**BACKGROUND AND SUMMARY OF THE INVENTION**

**Page 6, between lines 4 and 5, please insert the following header::**

**BRIEF DESCRIPTION OF THE DRAWINGS**

**Please amend the paragraph beginning on page 6, line 7 as follows:**

Fig. 1 [shows the] is a perspective view showing a laser according to the invention with cooling means at both ends [in a perspective general view];

**Please amend the paragraph beginning on page 6, line 9 as follows:**

Fig. 2[,] is a perspective view of the laser according to the invention [for external cooling circuit in a partial sectional view] with the cooling fins removed and portions thereof broken away, where the two electrodes with cooling medium channels, as well as the structure of the end pieces with flexible bearings, can be seen;



**On pag 6, betw n lin s 18 and 19, please insert the following header:**

**DESCRIPTION OF THE PREFERRED EMBODIMENTS**

**Please amend the paragraph beginning on page 7, line 13 as follows:**

This makes it possible, by means of the adjusting screws 20, to adjust the end pieces, which as shown in Fig. 2, each [bear] support one of the two electrodes fastened on the outer (movable) section 24, by means of the adjusting screws 20 in the angular position to the other electrode in each instance (in Fig. 2) to the electrode 36, which is fastened at the left end.

## ATTACHMENT FOR CLAIM AMENDMENTS

The following is a marked up version of each amended claim in which underlines indicates insertions and brackets indicate deletions.

1. (AMENDED) A CO<sub>2</sub> slab laser having a gas-filled chamber [limited] defined by a tubular housing (10), with at least two electrodes that extend into the tubular housing, said electrodes [overlap] overlapping one another and [form] forming a discharge chamber, and [with] resonator mirrors provided within said housing, characterized in that

[- the] said electrodes are each [held] supported at the opposite ends of [the] said tubular housing,

[- the] said mirrors are [arranged] supported in stationary relationship relative to the electrodes and

[- the] said electrodes[, jointly with the] and mirrors[,] are adjustable relative to one another.

2. (AMENDED) A CO<sub>2</sub> slab laser having a gas-filled chamber [limited] defined by a tubular housing, with at least two electrodes that extend into the tubular housing, said electrodes [overlap] overlapping one another and [form] forming a discharge chamber, and [with] resonator mirrors provided within said housing, characterized in that

[- the] said electrodes are each [held] supported at the opposite ends of [the] said tubular housing,

[- the] said mirrors are designed in one piece with [the] said electrodes and

[- the] said electrodes[, jointly with the] and mirrors[,] are adjustable relative to one another.

3. (Amended)      A CO<sub>2</sub> slab laser [according to Claim CO<sub>2</sub> slab laser] having a gas-filled chamber [limited] defined by a tubular housing (10), with at least two electrodes that extend into the tubular housing, said electrodes [overlap] overlapping one another and [form] forming a discharge chamber, and [with] resonator mirrors provided within said housing, characterized in that

[- the] said electrodes each are held at the opposite ends of [the] said tubular housing,

[- the] said mirrors are [arranged] supported in stationary relationship relative to [the] said electrodes and

[- the] said electrodes[, jointly with the] and said mirrors[,] are adjustable relative to one another.

5. (Amended)      A CO<sub>2</sub> slab laser according to Claim 3, characterized in that the electrodes are designed in one piece with the end pieces.

9. (Amended)      A CO<sub>2</sub> slab laser according to Claim 7, characterized in that the flexible bearing is a bellows.

11. (Amended)      A CO<sub>2</sub> slab laser according to Claim 9, characterized in that the adjusting elements contain piezoelectric crystals which are capable of being driven electrically.